

# DLG V2.2 for OpenTX: Upgrade notes

## Changes in 2.2

'Safe Zoom Exit' is improved for V2.2 and is now fully integrated. If the stick is away from the zero position when exiting Zoom, a warning sounds, and the next lower priority flight mode is selected (Cruise, Thermal1, Thermal2, or Speed). The brake stick will only be active after it's returned to the zero position.

## Upgrade instructions

If you already have DLG v2.1 installed, then you can add this feature without the need to start from scratch. There are just four steps. Remember to backup the model before making changes.

### Step 1 of 4: Copy extra sound file

An additional sound file is required for the brake alert. To install, open **DLG\_220.zip**, and extract the file **dl1brk.wav**. Then copy the extracted file to the **\SOUNDS\{language}** folder on the transmitter's SD card. For example, if your language is 'en', copy to **\SOUNDS\en**

### Step 2 of 4. Add special functions

Insert two new special functions into the specified slots:

SF12 L20 - Play Sound (Warn1) repeat(3s)

SF16 L20 - Play Track (dl1brk) repeat(3s)



### Step 3 of 4. Add logical switches

Insert four new logical switches into the specified locations:


L15 !L12 AND !L14

L16 Sticky(FM2, L15)

L17 L12 AND !L16

...

L20 ( L12 AND !L14 ) AND L16 Delay(2s)



### Step 4 of 4. Edit Landing FM

For FM4:Landing mode, change the activating switch from L12 to L17:

